

AMSOIL Online Product Application Guide

For best print results, use the print button below.



2008 Am General HUMMER H3 3.7L 5-cyl Engine Code [E]

LUBRICANTS & FLUIDS:

Engine Oil

Grade 1.....SEO23

Maximum Performance Signature Series 5W-30 Synthetic Motor Oil (ASLQT)

Performance Plus XL 5W-30 Synthetic Motor Oil (XLFQT)

Performance OE 5W-30 Synthetic Motor Oil (OEFQT)

All TEMPS.....5W-30

Manual Transmission,AR5 (RWD).....GL-3

All TEMPS.....75W-90 [1]

Manual Transmission & Transaxle Gear Lube 75W-90 (MTGPK)

Manual Transmission,AR5 (4WD).....GL-3

All TEMPS.....75W-90 [1]

Manual Transmission & Transaxle Gear Lube 75W-90 (MTGPK)

Automatic Transmission,4L60-E.....AF6 [2]

Signature Series Fuel-Efficient Synthetic Automatic Transmission Fluid (ATL) (ATLPK)

OE Fuel-Efficient Synthetic Automatic Transmission Fluid (OTLQT)

Differential, Rear.....SL136 [3]

All TEMPS.....

Severe Gear® 75W-90 (SVGPK)

Differential, Front.....SL136 [3]

All TEMPS.....

Severe Gear® 75W-90 (SVGPK)

Transfer Case,U/K TRC.....AF6

Signature Series Fuel-Efficient Synthetic Automatic Transmission Fluid (ATL) (ATLPK)

OE Fuel-Efficient Synthetic Automatic Transmission Fluid (OTLQT)

Fluids

Clutch Fluid.....HB

DOT 3 and 4 Brake Fluid (BFLVCN) [4]

Brake Fluid.....HB

DOT 3 and 4 Brake Fluid (BFLVCN) [5]

Power Steering Fluid.....PS004

Power Steering Fluid (PSFCN)

[1] Use GM P/N 89021806 or equivalent.

[2] This specification has been updated from Dexron II or III to Dexron VI per a Technical Service Bulletin from the manufacturer

[3] Use synthetic axle lubricant P/N 88900401 which replaces previously recommended synthetic axle lubricant P/N 89021677, Canada P/N 89021678 meeting GM Specification 9986115.

[4] Hydraulic Brake Fluid, DOT 3 P/N 12345347, spec. 9985642

[5] Hydraulic Brake Fluid, DOT 3. Original recommendation P/N 12377967 has been replaced by P/N 19353126.

 **FILTERS:**

Oil Filter	AMSOIL Oil Filter (EAO64)	[1]
Oil Filter	WIX 51522 Oil Filter	[2]

[1] Replaces the EaO30, which will still work for this vehicle

[2] Manufacturer OE Recommended Oil Change Intervals

 **CHASSIS LUBRICATION:**

4 Fittings, 0 Plugs.....LB

Synthetic Multi-Purpose Grease NLGI #2 (GLC3P)

Synthetic Water Resistant Grease (GWR3P)

DOMINATOR® Synthetic Racing Grease (GRGCR)

 **CAPACITIES:**

Engine, with filter.....5.7 liters [1]

Cooling System, Initial Fill.....9.5 liters

Passenger Car & Light Truck Antifreeze & Coolant

AMSOIL Antifreeze and Engine Coolant

Automatic Transmission, 4L60-E Initial Fill.....4.7 liters

Automatic Transmission, Total Fill

4 speed 4L60-E.....10.6 liters

Manual Transmission, AR5 (RWD).....2.2 liters

Manual Transmission, AR5 (4WD).....2.3 liters

Differential, Front.....1.4 liters

Differential, Rear.....2 liters

Transfer Case, U/K TRC.....1.5 liters

[1] After refill check oil level.

 **TORQUES:**

Oil Drain Plug.....19 ft/lbs

Manual Transmission

Fill Plug 27 ft/lbs

Drain Plug 27 ft/lbs

Transfer Case

Fill Plug 12 ft/lbs

Drain Plug 12 ft/lbs

 **OTHER TOP QUALITY PRODUCTS:**

By-Pass Oil Filters

Diesel Injector Clean

Cold Flow Improver

Cetane Boost Diesel Fuel Additive

PI Performance Improver Gasoline Additive

Product Recommendations and Drain Interval Chart